

Tron 60GPS

EPIRB with float-free and manual bracket



- Global sales and support network
- Antenna mounted LED for increased visibility
- Integrated GPS ensures accurate positioning
- Compatible with MEOSAR
- 7 year battery life
- 5 year warranty

Tron 60GPS

A compact and tamper-proof GMDSS EPIRB

Tron 60GPS is small and compact, and supplied either with a manual or a float-free bracket. This EPIRB is totally sealed and has 5 year warranty. Tron 60GPS has optimal visibility with a high-intensity LED located at the top of the antenna.

Specifications

| PARAMETER | |
|---------------------------|--|
| Battery | Lithium iron disulfide, 12 V/2900 mAh 7 year service life |
| Dimensions | H: 340 mm, W: 128 mm |
| Weight | 700 g |
| Material | Glass reinforced polycarbonate |
| Compass safe distance | 0.85 m |
| Temperature range | Operating: -20°C to + 55°C Storage: -30°C to +70°C |
| Operating life | Minimum 48 hours at -20°C |
| Cospas-Sarsat transmitter | Frequency: 406.037 MHz, output power: 5 W |
| Homing transmitter | Frequency: 121.500 MHz |
| Protocols | Maritime with MMSI, Maritime with Radio Call Sign, Serial Number and Radio Call Sign |
| Navigation device | 56 channel GPS receiver |
| Standard | IEC 61097-2 Ed.3, IEC 60945 Ed.4 |
| ACCESSORIES | |
| Brackets | Float-free FB-60 and manual MB-60 |
| Battery | Replacement kit |
| Hydrostatic release | HRU kit |
| WARRANTY | 5 year |

Float-free and manual bracket



Approved:

FCIC

Approval pending: CE/RED